

2.03

PRESSOSTATI - IP 65

VALVOIND Srl Via Pascoli, 5 - 24060 Bagnatica (Bergamo) Tel. 035.681919-Fax. 035.684461

Valvoind

valvole industriali

AS 501

PRESSOSTATI TRAFAG IP 65

codice	modello	range	differenziale		press.	temp.	Volt / Ampere		sensore	materiale	Ø
		Pressione bar	fisso bar	regolabile bar	max bar	max °C	AC	DC			
AS50601	P 1.5	-0.9..+1.5	0.1		10	150	500 V 10 A	30 V 15 A	soffietto	Ottone	1/4"
AS50602	P 2.5	0.2..2.5	0.1		10	150					
AS50603	P 4	0..4	0.2		12	150					
AS50604	P 6	0..6	0.2		12	150					
AS50605	P 10	1..10	0.4		24	150					
AS50606	P 16	1..16	0.4		24	150					
AS50607	P 25	2..25	1.0		40	150					
AS50608	P 40	4..40	1.0		40	150					
AS50701	PS 1.5	-0.9..+1.5	0.1		10	150	500 V 10 A	30 V 15 A	soffietto	Ottone	1/4"
AS50702	PS 2.5	0.2..2.5	0.1		10	150					
AS50703	PS 6	0..6	0.2		12	150					
AS50704	PS 16	1..16	0.4		24	150					
AS50705	PS 40	4..40	1.0		40	150					
AS50801	PV6	0..6		0.4..3.2	12	150	500 V 10 A	30 V 15 A	soffietto	Ottone	1/4"
AS50802	PV16	1..16		1..7.5	24	150					
AS50803	PV40	4..40		3..18	40	150					
AS50901	PVF 1.5	-0.9..+1.5		0.06..0.2	10	150	500 V 10 A	30 V 15 A	soffietto	Ottone	1/4"
AS50902	PVF 2.5	0.2..2.5			10	150					
AS50903	PVF 6	0..6		0.2..0.6	12	150					
AS50904	PVF 16	1..16		0.5..1.6	24	150					
AS51001	PK 10	1..10		0.45..0.9	100	135	500 V 10 A	30 V 15 A	pistone	INOX	1/4"
AS51002	PK 40	4..40		1.8..3.4	200	135					
AS51003	PK 100	10..100		3.2..7.5	200	135					
AS51004	PK 250	25..250		5.2..16	400	135					

AP 520

PRESSOSTATI DIFFERENZIALI TRAFAG

AS52001	PSTD 4	-1..+6	0..+4	0,2	8		250 V	24 V	soffietto	Ottone	1/8"
AS52003	PSTD 6	-1..+8	0..+6	0,3	12		10 A	2 A			
AS52101	PD 3,4	-0,6..+3,4		0,16	12	150	500 V	30 V	soffietto	Ottone	1/8"
AS52102	PD 6	0..6									
AS52103	PD 16	1..16									



AS 900

PRESSOSTATI PER CENTRALI TERMICHE

codici	Modello	Range	IP	attacco	Descrizione
AS95101	B12CN	0..8 BAR	IP40	1/4"	Pressostato di regolazione
AS95102	B12CRNY	0..8 BAR	IP65	1/4"	
AS95103	B12DNY	5..16 BAR	IP65	1/4"	
AS95104	B12FNY	12..50 BAR	IP65	1/4"	
AS95105	B12GNY	25..150 BAR	IP65	1/4"	
AS95106	B12HNY	60..300 BAR	IP65	1/4"	
AS95201	B01CM	3..7 BAR	IP40	1/4"	PRESSOSTATI A RIAMO MANUALE omologato ISPESL
AS95202	B12MN	1..5 BAR	IP40	1/4"	

